

F3 RE 15 LR F3 RE 20 LR

RETRACTABLE LEVEL-RIDE

WITH ALUMINIUM GUIDES

LOAD CAPACITY: 1500, 2000 KG



DESCRIPTION

F3 RE 15/20 LR is especially suited to Roll Cage operations, but more specifically to the typical British food industry operator.

Anteo superb guide rail system eliminates any 'Racking or Bounce' of the lift frame and platform during deployment and retraction.

Available with tilt cylinders to set the platform at any level, a must where the operator loads or unloads on gradients (option).

SPECIFICATIONS

Platform:	Aluminum (1 piece) Steel+Aluminum (single fold)
Platform depth:	from 1300 to 1900 mm rear bumper EEC type approved
Lift cyliders:	2
Tilt cylinders:	2 (option)
Autotilt at ground:	none - levelride
Sliding system:	Alloy guides and hydraulic motor
Power supply:	12 or 24 V
Low maint. bushes:	greasable
Frame color:	Black KTL plus and powder paint
Weight:	from 502 Kg

SUGGESTED OPTIONS

- Inside body remote control;
- Radio remote control;
- Foot operated controls on platform;
- Tilt cylinders;
- Front ramps;
- Side ramps













F3 RE 15 LR F3 RE 20 LR

RETRACTABLE LEVEL-RIDE

WITH ALUMINIUM GUIDES


LOAD CAPACITY: 1500, 2000 KG


TECHNICAL DATA

TEGINIOAE DATA								
		1 Fold platform (steel + aluminum)						
				3 way hinged ramps to front	fixed leading edge			
Mod.	Load capacity (centre of gravity at 600 mm)	Total depth (V)	Н	Z	Z	Mounting space		
F3 RE 15 LR	1500 Kg	1516 1716 1916	616 716	900 1000	920 1020	1583 1683		
F3 RE 20 LR	2000 Kg		816	1100	1120	1783		

1 Piece platform					
aluminium platform with 3 way hinged ramps to front					
Total depth (V)	Mounting space				
1300 1500 1800	2256 2456 2756				

All dimension in mm unless otherwise specified. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.








LOW MAINTENANCE BUSHES AND CHROMIUM PLATED PINS.



POWDER COATING PAINT (2) ADDED TO KTL PLUS (1). NO RUST AND NO SALT STAINS.



HI-TENSILE ALUMINUM SPECIALISTS SINCE 1992.



LOW NOISE POWER UNIT & NO ELECTRONICS = EASY MAINTENANCE







