



## F3 CL 076

### CANTILEVER TAIL-LIFTS

LOAD CAPACITY: 750 KG



#### DESCRIPTION

The 3 cylinders F3 CL 076 is a very light strong and compact lift, with very high performances. Smooth hydraulic automatic tilt. High stiffness ideal to equip vehicles for customers that like high performances. The F3 CL 076 is available with a wide variety of quick-fit mounting plates, to suit most commercial vehicles and light trucks up to 6.5T GVW. Main beam: tailor made to suit most commercial vehicles such as:

- Fiat DUCATO - Citroen JUMPER - Peugeot BOXER
- Ford TRANSIT
- Iveco DAILY
- Mercedes Benz SPRINTER
- Renault MASTER - Opel MOVANO
- Volkswagen CRAFTER - Man TGE

#### SPECIFICATIONS

Platform:	Aluminium
Platform depth:	from 1600 to 2000 mm rear bumper EEC type approved
Lift cylinders:	1
Tilt cylinders:	2
Autotilt at ground:	hydraulic (with memory feature)
Platform opening:	Gravity opening
Power supply:	12 or 24 V
Low maint. bushes:	greasable
Frame color:	Black KTL plus and powder paint
Weight:	from 178 Kg

#### SUGGESTED OPTIONS

- Inside body remote control;
- Radio remote control;
- Foot operated controls on platform;
- Blinking lights on platform;
- Roll stop;
- Platform lock handle;
- Body seal kit





# F3 CL 076

## CANTILEVER TAIL-LIFTS

LOAD CAPACITY: 750 KG

### TECHNICAL DATA

Mod.	Arm width	Load Capacity (600 mm load centre)	Standard platform dimension		Weight* (Kg)	Floor to ground (max)	Floor to bottom of chassis		Mounting space	
			Depth	Width			min	max		
F3 CL 076 C	W44 (440 mm)	750 Kg	1200	on demand	205	980	240	420	441	
F3 CL 076 C1			1400		225		280		480	485
F3 CL 076 H			1600		245		300		530	550
			1800		285					


\*Approximate weight for tail-lift equipped with aluminium platform dimensions 1400 x 2200 mm. The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.

### PLATFORM OPENING STANDARDS

- **Gravity Open:** for FCLO76 **(as standard)**

**ALUMINUM REAR BUMPER BAR** up to 3,5T GVW


**STEEL REAR BUMPER BAR** up to 6,5T GVW



LOW MAINTENANCE BUSHES AND CHROMIUM PLATED PINS.



POWDER COATING PAINT (2) ADDED TO KTL PLUS (1). NO RUST AND NO SALT STAINS.



HI-TENSILE ALUMINUM SPECIALISTS SINCE 1992.



LOW NOISE POWER UNIT & NO ELECTRONICS = EASY MAINTENANCE



01/2021