

F3 CLA30 . SPECIAL TAIL-LIFTS FOR ANIMALS **5 CYLINDERS**

- 3000 KG AT 600 MM 2500 KG AT 1000 MM



Safety gates and anti-skid not supplied

TECHNICAL SPECIFICATIONS

Cylinders:	2 lift cylinders + 2 tilt cylinders + 1 automatic tilt cylinder	f F
Tilt cylinders:	Double acting	ا ا
Platform inclination:		
(100 mm)	of max.	
Platform opening:	Powered opening	
Automatic tilt at ground level:	Yes, Hydraulic	
Platform material:	Aluminium or steel	
Platform overlap under floor:	-75 mm	
Standard platform depths Steel:	Not available	
Standard platform depths Alu:	2600 mm	
Standard platform widths Steel:	Not available	
Standard platform widths Alu:	2450 mm (max 2600) 2520 mm (max 2600)	
Lift arm lengths:	HS	
Lift arm widths (W):	1250 mm	

Unit Exterior control box with joystick, turn button

Standard control:


Weights incl. CE bumper

APPLICATIONS

The tail lift F3 CLA3O is the ideal tail lift for use in animals transportation.

F3 CLA30 is suitable for trucks, semitrailers and vehicle with low drawbar coupling.





Mod. (Load capacity (centre of gravity at 600 mm)	Std. Platform Dimensions		Weight	Е	ЕА		В	В'		Arm	Arm Width (centre to centre)
		Depth	Width	Kg	max	min	max	min	min	' L	Length	W 125
F3 CL 30 HS	3000 kg	2600	2500	670	1240	470	520	810	960	295	1003	1250

^{*}Indicative weight of tail-lift supplied in kit without rear bumper and with a 1800 mm depth platform.

The weight may vary according to width.

All dimensions are in mm unless otherwise specified. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.